



KEI has been at the forefront of India's wire and cable industry for the last 5 decades. We manufacture a range of specialized cables and are a crucial player in the domestic and retail segment. Since inception, we have firmly believed in the philosophy of constant growth and innovation. Customer satisfaction has always been our priority. A highly qualified, committed and experienced group of professionals strive to meet international standards and cater to the needs of a changing market. Our unblemished track record has earned us the patronage of leading industrial houses, project consultants and architects. In order to provide reliable and expedient services to our customers,

we have created manufacturing facilities at Rakholi, Chinchpada (Silvassa), Chopanki, Bhiwadi & Pathredi (Rajasthan). We employ state-of-the-art equipment and adhere to international safety and environmental norms. KEI was established in 1968 as a partnership company in the domestic wire segment. In the early seventies we started manufacturing switchboard cables and control, instrumentation and thermocouple extension cables including special application cables like fire retardant and low halogen cables. In 1993 we added power cables with PVC & XLPE insulation in our product line. Today KEI is a one-stop-shop when it comes to meeting cabling requirements for the domestic, power and industrial sectors.

KEI Industries Limited

REGISTERED AND CORPORATE OFFICE:

D-90, OKHLA INDUSTRIAL AREA PHASE-I, NEW DELHI-110020, TEL: +91-11-26818840/8642/0242 FAX: 26817225, 26811959

E-MAIL: info@kei-ind.com WEBSITE: www.kei-ind.com CIN NO: L74899DL1992PLC051527

Manufacturing Units		
Bhiwadi KEI Industries Limited SP-919/920/922, Ricco Industrial Area, Phase-III, Bhiwadi, Distt. Alwar-301019 Rajasthan Tel: +91-1493-22014/2201731 Fax: 221731 E-Mail: bhiwadi@kei-ind.com	Silvassa KEI Industries Limited 99/2/7, Madhuban Industrial Estate, Rakholi, Silvassa-396230 Dadra & Nagar Haveli Tel: +91-260-264440/2630944 Fax: 2645896 E-Mail: silvassa@kei-ind.com	Chopanki KEI Industries Limited A-280/281/282/283/284, Ricco Industrial Area (Chopanki) Distt. Alwar-301019 Rajasthan Tel: +91-1493-260202/206 Fax: 260203 E-mail: chopanki@kei-ind.com
Pathredi KEI Industries Limited Plot No.SP2-874, Ind. Area Pathredi-301019 Bhiwadi (Alwar) Rajasthan (India) Tel: 9828588579	Chinchpada KEI Industries Limited Survey No. 1/1/2/5, Village Chinchpada, Silvassa-396230, Dadra Nagar Haveli (UT) Tel: 7574881215 E-Mail: silvassa@kei-ind.com	
Marketing Offices (India)		
WEST		
Marketing Office-Mumbai KEI Industries Limited Nirvan Corporate, 7th Floor, Opposite Aghadi Nagar, Pump House, Jijamata Road, Andheri East, Mumbai-400093 Tel: +91-22-28239673, 28375642 Fax: +91-22-28258277 E-mail: mumbai@kei-ind.com	Vapi/Silvassa/Daman KEI Industries Limited A1/302, Karmabhumi Residency, Behind Golden Bakery, Nanakwada, Halar, Velsad-396001 Mr. Harsh Desai, Tel: 9723455316 E-Mail: harsh.desai@kei-ind.com	Nasik KEI Industries Limited 4, Sanket Apartment, Tidake Colony, Behind Hyundai Showroom, Nashik, Maharashtra-422002 Tel: 8905369705 / 8291918949 E-Mail: ghanshyam.pardeshi@kei-ind.com
Ahmedabad KEI Industries Limited 301, Sarthik Complex, Opp. ISCKON BRTS, Satellite Road, Ahmedabad-380015, Tel: 9825795673 E-mail: dhamin.maniar@kei-ind.com , ahmedabad@kei-ind.com	Raipur KEI Industries Limited 206, 2nd Floor, Harshit Corporate, Amanaka, G.E. Road, Raipur, Chhattisgarh-492001 Email: Chhattisgarh@kei-ind.com Mr. Sumit Ganguly - 7581808898 Email: sumit.ganguly@kei-ind.com	Baroda KEI Industries Limited 803-804, Siddharth Complex, Near Hotel Express R.C. Dutt Road, Baroda-390007 Tel: +91-265-6539719, 2341831, 9824676443, 9327476732, E-Mail: baroda@kei-ind.com , amit.gohil@kei-ind.com
Pune KEI Industries Limited Vasudha Equinox, Office No. 104, 1st Floor, Mouje Bopodi, Near Khadki Railway Station, Pune-411003 Tel: 9922722378 E-Mail: srivastav.prashant@kei-ind.com	Goa KEI Industries Limited House no: 617, Housing Board Colony, Camurim Mapusa Goa 403507. E-Mail: goa@kei-ind.com Mr. Nilesh Parab - 9890452484 E-Mail: nilesh.parab@kei-ind.com	Surat KEI Industries Limited 703, Royal Trade Centre, Opposite Star Bazar, Adajan-Hazira Road, Adajan, Surat-395009 Tel: 09879018448, +91-261-2793279 E-Mail: rakesh.patel@kei-ind.com
Nagpur KEI Industries Limited 103, Misal Layout, Near Maharashtra School Nagpur - 440014 E-Mail: nagpur@kei-ind.com Mr. Saranjeet S. Kohli, Tel: +91-9822473774 E-Mail: saranjeet.kohli@kei-ind.com	Solapur KEI Industries Limited Niranjan V. Deshpande 462, Om Namah Shivay Nagar, Kumbhe Road, Near Shastri Math, Hatture Vasti, Solapur, 413005 Tel: 8291918937 E-Mail: niranjan@kei-ind.com	Aurangabad KEI Industries Limited Mahesh Pandurang Akalekar, Flat No. 11, Padmini Housing Society, Nakshtra Park, Beside Walmi Naka, Patthan Road, Aurangabad- 431 005 Tel: 070459227077706, 9075008151 E-Mail: aurangabad@kei-ind.com , mahesh.akalekar@kei-ind.com
Kolhapur KEI Industries Limited, 776/ 3/6 AmarnathHights Building, Near AmarnathMandir Ganesh Colony, Kalamba Road, Kolhapur - 416007 Mr. Rajaram B. Kamble Tel: 9371104263 / 8291918940 E-Mail: kolhapur@kei-ind.com , rajaram.kamble@kei-ind.com	Rajkot KEI Industries Limited Mr. Nitin Tank Tel: +91-8155044144 E-Mail: nitin.tank@kei-ind.com	
NORTH		
Jaipur KEI Industries Limited Shivam Business Center, 405, 4th Floor, Calgary Hospital Road, Pradhan Marg, Malviya Nagar, Jaipur - 302017 (Rajasthan) Phone No. + 91 141 5179279 Fax: +91 141 252 9404 Tel: +91 99290 93711 E-Mail: jaipur@kei-ind.com	Lucknow KEI Industries Limited E-79,80,81 Transport Nagar (Kanpur Road) Lucknow (UP)-226012 Tel: 0522-4010752 E-Mail: up@kei-ind.com	Noida KEI Industries Limited A-43 Ground Floor, Sector-64, Noida, UP-201301 Tel: 0120-4315467
Chandigarh KEI Industries Limited SCO 17, 1st Floor, Swastik Vihar, MDC, Sector-5, Panchkula-134109 Tel: +91-172-4416301, 4416300, 9872974986, 987251222 E-Mail: chandigarh@kei-ind.com	Kanpur KEI Industries Limited 15/240 F, In Front of Hotel Attic, Civil Lines, Kanpur (UP)- 208001 Tel:- 9935062910	Indore KEI Industries Limited Plot No 451 Sch No 78 Industrial Area New Loha Mandi Dewas Naka Indore 452010 (M.P.) Tel: 9826588865
	Panipat KEI Industries Limited JP Tower, First Floor, Tau Devi Lal Complex Panipat-132013 Tel: +91-8050417107 E-mail: shakti.sharma@kei-ind.com	Gurgaon KEI Industries Limited Shop no-101 1st Floor, Radha Palace Gurudwara Road, Gurgaon Haryana-122001 Tel: +919873561757 E-Mail: rk.singh@kei-ind.com
SOUTH		
Chennai KEI Industries Limited No.4, (Old. No. 23) SIR C P Ramasamy Road, 2 nd Floor, Near Apollo Spectra Hospital Alwarpet, Chennai-600018 Tel: +91-44-42009120 Fax: +91-44-42009130; 8939768405 E-Mail: victor@kei-ind.com , chennai@kei-ind.com	Bangalore KEI Industries Limited No 15, Sirur Park Road, Sheshadripuram, Bangalore-560020 Tel: +91-80-23466254, +91-80-23466260/55 Ph.: 8884439333 E-Mail: bangalore@kei-ind.com	Secunderabad KEI Industries Limited 5-2-510, 2nd floor, plot no: 44, Beside Govt Primary School, Near Bible House, Hyderabad, R.P. Road, Secunderabad, Telangana- 500003 Tel: 8008000583, 9963530111 E-Mail: kiran.kumar@kei-ind.com
Cochin KEI Industries Limited Ward No.18/555 and 19/556, NAD Thorappu, Near Kuzhikkattukara Jama Masjid, Edathala, Ernakulam, Kerala - 683563 Tel: 9645096420, E-Mail: cochin@kei-ind.com	Hyderabad KEI Industries Limited Plot No. 76, H.No. 3-14-52/1, Shubodaya Colony, Near M.E Reddy Function Hall, Mansoorabad, Vanasthalipuram, Hyderabad-500070 Tel: +91 88860 63702, +91 99855 77886 E-Mail: hyderabad@kei-ind.com	Coimbatore KEI Industries Limited, SF.No. 581/A, K.N.G. Pudur Road, Kanuvai Post S.M. Palayam Village, Coimbatore-641108 Tel: 9443324217, E-Mail: manohar.s@kei-ind.com
	Guwahati KEI Industries Limited, Mangalam Plaza Compound, Near North East Weight Bridge, NH-37 Bye Pass, Bellola, Guwahat-781029 Assam Rubiul Gogoi – 8134846024, 9706050041 E-Mail: rubul@kei-ind.com	Vijayawada KEI Industries Limited Venkata Ramana Enclave, D.No. 48-18-2a/1, 2nd Floor -Nagarjuna Nagar Colony, 6th Lane, Behind Sai Baba Temple, Besides Ayush Hospital Krishna Dist., Andhra Pradesh-520008 Tel: 8886063715 E-Mail: syed.mahamood@kei-ind.com
Patna KEI Industries Limited HIS Plot No-4H/59, Bahadurpur Housing Colony, Lohia Nagar, Agamkuan, Patna 800026, Bihar Tel: + 91 95348 38038, 7360042598 E-Mail: bihar@kei-ind.com	Ranchi KEI Industries Limited Golden Camp Warehouse, Old H B Road Kokar, Ranchi, Jharkhand - 834001 Tel: 9810492658, 8918904901 E-Mail: jharkhand@kei-ind.com	Kolkata KEI Industries Limited Arihant Benchmark, 4th Floor 113-F Matheshwartola Road Ps:Tiljala, Kolkata: 700046 Tel: 033-4062 0820 / 4062 0822, 9932449183 E-Mail: kolkata@kei-ind.com
Bhubaneswar KEI Industries Limited Plot No- 139, 3rd Floor, Rose Dale District Centre, Chandrashekharpur, Bhubaneswar-751016, Odisha Tel: 9937033537 E-Mail: odisha@kei-ind.com		Siliguri KEI Industries Limited, 8, Balai Das Chatterjee Road, Ground Floor, Hakimpura, (Opp. Relief Physiotherapy Centre) Dist-Darjeeling, Siliguri-734001, West Bengal Tel: 6292209625, E-Mail: dibyoyoti.karmakar@kei-ind.com
Marketing Office (Overseas)		
Dubai KEI Industries Limited Post Box No. 261739, Jebel Ali Free Zone, Dubai, U.A.E. Tel: +9714 881 2310, +971 50 2112013 Fax: +9714 881 2311 E-mail: keidubai@emirates.net.ae / dubai@kei-ind.com Contact: Mr. Shri Tamhankar	Singapore KEI Industries Limited No.52, UBI Avenue 3, # 04-37 Frontier, Singapore-408667 Tel: +65 83240183 Contact: Mr. Xavier Toh Hong Ghee E-mail: xavier@kei-sin.com	Korea (Local Representative) Contact: Mr. CH Han E-mail: ch.han@kei-ind.com Tel: +82-10-4351-8585 Mr. TH Park E-mail: th.park@kei-ind.com Contact : +82-10-9104-4519
South Africa KEI Cables SA (Pty) Ltd. Unit 27-4, Fish Eagle View, 1 Benacre Lane, Modderfontein, 1698, South Africa Ms. Thavashnee Pillay +27 83 235 2895	Nigeria (Marketing Representative) E-mail: kunal.gupta@kei-ind.com Tel: +234 809 9777786	



KEI

Wires & Cables



HAR TENSION SAHE, CHALTI RAHE

KEI Wires pass through 15 strict quality tests before reaching your home.



IS : 694



CM/L-7390172

IS : 694



CM/L-7800072614



*Subject to standard product usage as per IS-694 product specifications.



homecab™ - FR

Flame Retardant

Test	Specification	Specified Values
Critical Oxygen Index	ASTM-D 2863	Minimum 29%
Temperature Index	ASTM-D 2863	Minimum 250 °C

SIZE DIMENSIONS AND RATINGS

Nominal Cross Sectional Area of Conductor	Number/Nominal Dia of wires* [Nom.]	Thickness of insulation [Nom.]	Overall Diameter Max.	Current Rating		D.C Resistance [Max.] at 20 °C
				Casing	Concealed	
Sq.mm	Number/mm	mm	mm	amps	amps	Ohm/km
0.5	16/0.2	0.6	2.6	6.00	5.00	39.0
0.75	24/0.2	0.6	2.8	7.50	7.00	26.0
1.00	32/0.2	0.6	3.0	12.00	11.00	19.5
1.50	30/0.25	0.6	3.4	16.00	14.00	13.3
2.50	50/0.25	0.7	4.1	22.00	19.00	7.98
4.00	56/0.3	0.8	4.8	29.00	26.00	4.95
6.00	84/0.3	0.8	5.3	37.00	31.00	3.30

*The number & diameter of conductor strands are for reference only and governed by conductor resistance.

*The above data is indicative only and may be revised without prior information. KEI will not be responsible for any damages arising out of incorrect application of its product.



FLAME RETARDANT PVC INSULATED SINGLE CORE UNSHEATHED COPPER CABLES (UP TO 1100 VOLTS AC)

CONDUCTOR: The conductors, drawn from bright electrolytic grade copper and annealed and bunched together.

INSULATION: The bunched conductors are insulated with specially formulated FR PVC compound with a high insulation resistance value. The insulation process is carried out on modern high speed extrusion lines, which ensures high accuracy and consistency in performance. Flame retardant properties enable the cable to withstand overloads. The insulation is resistant to boiling water, steam and vapors. This prevents ageing and cracking in kitchens, bathrooms, damp walls and chemical industries.

MARKING: The cables are printed with generic marking 'HOMECAB'.

COLORS: Red, Yellow, Blue, Black, Green and Grey.

PACKING: 90 Meters (apprx.100 yards) pack in protective cartons.

HomeCab is a multi-stranded flexible wire with flame retardant properties. It has specially formulated insulation with a high oxygen and temperature index, enabling the wire to withstand overloads preventing electric mishaps. So, give yourself the promise of security and supreme quality. Get KEI house wires and safeguard your home for life.



conFlame® - FR-LSH

Flame Retardant Low Smoke & Halogen

Test	Specification	Specified Values
Critical Oxygen Index	ASTM-D 2863	Minimum 29%
Temperature Index	ASTM-D 2863	Minimum 250 °C
Acid Gas Generation	IEC 60754 -1	Maximum 20%
Smoke Density Rating	ASTM-D 2843	Maximum 60%

SIZE DIMENSIONS AND RATINGS

Nominal Cross Sectional Area of Conductor	Number/Nominal Dia of wires* [Nom.]	Thickness of insulation [Nom.]	Overall Diameter Max.	Current Rating		D.C Resistance [Max.] at 20 °C
				Casing	Concealed	
Sq.mm	Number/mm	mm	mm	amps	amps	Ohm/km
0.75	24/0.2	0.6	2.8	7.50	7.00	26.0
1.00	32/0.2	0.6	3.0	12.00	11.00	19.5
1.50	30/0.25	0.6	3.4	16.00	14.00	13.3
2.50	50/0.25	0.7	4.1	22.00	19.00	7.98
4.00	56/0.3	0.8	4.8	29.00	26.00	4.95
6.00	84/0.3	0.8	5.3	37.00	31.00	3.30

*The number & diameter of conductor strands are for reference only and governed by conductor resistance.

*The above data is indicative only and may be revised without prior information. KEI will not be responsible for any damages arising out of incorrect application of its product.

FLAME RETARDANT LOW SMOKE PVC INSULATED SINGLE CORE UNSHEATHED COPPER CABLES (UP TO 1100 VOLTS AC)

CONDUCTOR: The conductors, drawn from bright electrolytic grade copper and annealed and bunched together.

INSULATION: The bunched conductors are insulated with specially formulated Flame Retardant Low Smoke Compound. During a fire situation, the FR-LSH compound restricts the spread of flame. The smoke emission is also minimal.

MARKING: The cables are printed with generic marking 'CONFLAME'.

COLORS: Red, Yellow, Blue, Black, Green and Grey.

PACKING: 90 Meters (apprx.100 yards) pack in protective cartons.

KEI's innovative offering Conflame is ideal for wiring solutions in multi-storied buildings, hotels, hospitals, commercial establishments and residential complexes. It is shielded by a specially formulated flame retardant PVC compound. During fire, ordinary PVC emits black smoke and toxic fumes which are acidic in nature. This impairs visibility and hampers rescue operations. Conflame insulation retards spread of fire and emits minimum smoke and toxic gases. Thereby reducing the risk of injury. So, give yourself the promise of security and supreme quality. Get KEI house wires and safeguard your home for life.



banFire® - ZHFR

Zero Halogen Flame Retardant

Test	Specification	Specified Values
Critical Oxygen Index	ASTM-D 2863	Minimum 29%
Temperature Index	ASTM-D 2863	Minimum 250 °C
Acid Gas Generation	IEC 60754 -1	Maximum 0.5%
Smoke Density Rating	ASTM-D 2843	Maximum 20%

SIZE DIMENSIONS AND RATINGS

Nominal Cross Sectional Area of Conductor	Number/Nominal Dia of wires* [Nom.]	Thickness of insulation [Nom.]	Overall Diameter Max.	Current Rating		D.C Resistance [Max.] at 20 °C
				Casing	Concealed	
Sq.mm	Number/mm	mm	mm	amps	amps	Ohm/km
0.75	24/0.2	0.6	2.8	7.50	7.00	26.0
1.00	32/0.2	0.6	3.0	12.00	11.00	19.5
1.50	30/0.25	0.6	3.4	16.00	14.00	13.3
2.50	50/0.25	0.7	4.1	22.00	19.00	7.98
4.00	56/0.3	0.8	4.8	29.00	26.00	4.95
6.00	84/0.3	0.8	5.3	37.00	31.00	3.30

*The number & diameter of conductor strands are for reference only and governed by conductor resistance.

*The above data is indicative only and may be revised without prior information. KEI will not be responsible for any damages arising out of incorrect application of its product.

ZERO HALOGEN FLAME RETARDANT INSULATED SINGLE CORE UNSHEATHED COPPER CABLES (UP TO 1100 VOLTS AC)

CONDUCTOR: The conductors, drawn from bright electrolytic grade copper and annealed and bunched together.

INSULATION: The bunched conductors are insulated with specially formulated grade of Halogen Free Flame Retardant (ZHFR) compound is used. The insulation does not melt or drop in case of fire. The smoke emitted is transparent, non-toxic and minimal. The victims trapped in the fire do not suffocate and evacuation is convenient.

MARKING: The cables are printed with generic marking 'BANFIRE'.

COLORS: Red, Yellow, Blue, Black, Green and Grey.

PACKING: 90 Meters (apprx.100 yards) pack in protective cartons.

KEI Banfire is processed using a zero Halogen Flame Retardant compound (ZHFR). The insulation is of superior quality, 100% PVC free and eco-friendly. In case of a fire situation, Banfire does not emit toxic or poisonous fumes, which enables safe evacuation. These wires are best suited for wiring in hospitals, hotels, business establishments and high rise buildings where fire can be determined. So, give yourself the promise of security and supreme quality. Get KEI house wires and safeguard your home for life.